

Midas NFC

Overview

Frequency Band

NFC 13.56 MHz

Chip

NXP NTAG213

Antenna Dimensions

10 x 17 mm / 0.39 x 0.67 in

International Standard

ISO 14443A

Industry Segments

Electronics and Gaming
Apparel

Applications

NFC
Gaming and Toys
Electronics

RoHs

EU Directive 2011/65/EU and
2015/863 Compliant

REACH

Regulation (EC) No 1907/2006



Ideal NFC performance for small products

Our Midas inlays and tags are designed for products with space restrictions. Due to its small footprint, Midas is well suited for applications where inlays are embedded within limited spaces. It is the perfect thin inlay for embedding into housing such as electronics pairing, NFC-Bluetooth pairing, brand authentication, toy figures, and key fobs.

Midas designed as a copper antenna is available with the NXP NTAG213 chip and comes with the unique ID (UID) mirror functionality, which enables the chip serial number to be mirrored as part of its encoded URL address. This feature allows every tag to be seen and read as unique from the application perspective, without requiring users to encode inlays with different numbers.

Midas products are based on the ISO 14443 A standard, and are compatible with NFC Forum standards. Our inlays and tags are compliant with ISO 9001:2015 Quality Management and ISO 14001:2015 Environmental Management. This ensures a reliable and state-of-the-art product that meets a variety of application needs.

Technical features

Chip	NXP NTAG213	
User Memory	144 bytes	
Product Code	3002647	3003265
Delivery Format	Wet inlay	Dry inlay
Die-cut Dimension	12 x 19 mm / 0.47 x 0.75 in	-
Inlay Substrate	PET	
Face Sheet	Clear PET	
Thickness	75 µm	
Total Thickness	157 µm	
Standard Pitch	24 mm / 0.945 in	
Web Width	24 mm / 0.945 in	
Core Size	76 mm / 3 in	
Quantity / Reel	5000 pcs/reel	5000 pcs/reel 20000 pcs/box
Operating Temperature	-25 °C to 70 °C -13 °F to 158 °F	

Contact information

rfid.averydennison.com/contact

North America: +1-866-903-7343 (toll free US)

International: +1-678-617-2359



© 2021 Avery Dennison Corp. All rights reserved. 170 Monarch Lane, Miamisburg, OH 45342, USA Third party trademarks and/or trade names used herein are the property of their respective owner(s). Some of the trademarks appear for identification purposes only.

Warranty: Please refer to Avery Dennison standard terms and conditions: rfid.averydennison.com/termsandconditions

Care and handling: RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics / RFID to keep environmental impact and static charge to a minimum.

Applications: This product should be tested by the customer / user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use. Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.