



Advanced Card Systems Ltd.
Card & Reader Technologies

ACR330-A Validator with QR code Scanner

Technical Specifications V0.08.00





1.0. Technical Specifications



Processor

ARM Cortex-A8 1GHz Processor

Operating System

Linux 4.4

Memory

Flash 4GB (Available space for user: 900mb)

RAM 512 MB

Tamper Protected RAM 32KB (for sensitive data storage with API provided)

Power

Power Source..... 9 V – 36 V

SuperCap Valid Time 5 seconds with full function after main power is removed

Connectivity

USB Host 2.0 Full Speed

Serial Port RS-232 x 1, RS-485 x 1

*GPS Supported with Internal or external antenna

Wi-Fi..... IEEE 802.11 b/g/n

*Cellular 4G/3G/GPRS

Ethernet Built-in 10/100-base-T Ethernet

Bluetooth..... Bluetooth 4.0 Dual Model

Contactless Smart Card Interface

Standard ISO 14443 A & B, Parts 1-4, MIFARE Classic®, MIFARE DESFire®, MIFARE Ultralight®, MIFARE Ultralight C®, MIFARE Plus®, Felica, Calypso

Protocol..... MIFARE Classic Card Protocols, T=CL

Operating Distance Up to 50 mm

Operating Frequency 13.56 MHz

SAM Card Interface

Standard ISO 7816 Class A, B and C (5 V, 3 V, 1.8 V), T=0 and T=1

SAM Card Slots..... 4 ID-000 slots

Card Connector Type..... Contact



Built-in Peripherals

Buttons.....	4 back-lit buttons
LCD Display.....	4.3-in TFT-LCD, 480 x 272 Colors
Touch Panel.....	Capacitive Type
Audio.....	3W Speaker, Buzzer
.....	Around 80 dB in 1 m distance
Buzzer.....	Supported
LED Transaction Indicators.....	Front: Blue, Orange, Green, Red
.....	Back: Green, Red
Memory.....	MicroSD memory card expansion slot
.....	Supports MicroSD memory card from 1 GB to 32 GB
Temperature Sensor.....	Supported

***Barcode Scanner**

Linear.....	Code 128, EAN, Code 39, UPC, Code 2 of 5, Interleaved 2 of 5, Codabar, etc
2D.....	PDF417, Data Matrix, QR Code
Illumination.....	White LED
Materials.....	Paper, Mobile phones and Tablets

Other Features

- Firmware Upgradable
- Tamper Switch (internal anti-intrusion detections and protection)
- Real-time Clock

Physical Specifications (Main Body)

Main Body Dimension.....	245 mm (H) x 135 mm (W) x 91mm (T)
Case Color.....	Grey and Black
Weight.....	1.08kg

Physical Specifications (Main Body + *Back Mount)

Main Body Dimension.....	245 mm (H) x 135 mm (W) x 159mm (T)
Case Color.....	Black
Weight.....	1.88kg
Pole Supported.....	31mm, 32mm, 35mm (Both Vertical and Horizontal)

Operating Conditions

Operation Temperature.....	-20 °C – 60 °C
Humidity.....	15% – 95 %, non-condensing
Shock and Vibration.....	Military Standard MIL-STD-810
Protection from dust & water.....	IP54

Certifications/Compliance

EMV[®]/PBOC Contactless Level 1, MasterCard[®] Contactless, Visa payWave[®], CE, FCC, RoHS 2

*Optional



ARM is a registered trademark of ARM Limited (or its subsidiaries) in the EU and/or elsewhere. All rights reserved.
 EMV™ is a trademark owned by EMVCo LLC.
 Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries.
 MIFARE, MIFARE Classic, MIFARE DESFire, MIFARE Plus, MIFARE Ultralight, MIFARE Ultralight C are trademarks of NXP B.V.
 Mastercard is a registered trademark, and the circles design is a trademark of Mastercard International Incorporated.
 VISA payWave is a registered trademark of Visa International Service Association.